

CPU Coolers

Xprovider Technology

Model: 772-60CU

- Fan Size: 70 x 70 x 15 mm
- Heat Sink Material: Cooper.
- Cpu Type: P4 Socket 478 up to 2.8G.
- Lead Wire: 3Pins power connector.
- Option: Lighting cooling fan with LEDs.
- Application: CPU cooling.



Cooling Fan Specification:

Fan Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Height
701512U	12VDC	10-14VDC	0.35A	4.20W	37.50CFM	1.20mm	4000RPM	24db	51g
701512H	12VDC	10-14VDC	0.37A	4.44W	40.50CFM	1.40mm	5000RPM	31db	51g
701512M	12VDC	10-14VDC	0.16A	1.92W	21.50CFM	1.25mm	3500RPM	25db	51g

Note: Standard cooling fan model is 701512U.

CPU Cooler Specification:

Model	Fan	Base	Folded Fin	CPU Type	Connector	Interface	Life
772-60CU	701512U	Cooper	Cooper	P4 2.8G	3 Pin	Thermal-Grease	50,000Hours

Option:

1. Standard fan model is Ultra High speed, Slight or Low speed fan on request.
2. Lighting Cooler with transparent cooling fan on request.

772-60CU with Cooper cooler base and folded fins, it's design for P4 Socket 478 up to 2.8G Hz.

772-60CU standard fan motor model number is 701512U, high and medium speed fan motor are recommend for lower CPU frequency only.

On customers request, Xprovider also providing colorful lighting cooler with superbright LEDs and transparent cooling fan body.

CPU Coolers

Xprovider Technology

Model: 772-67CU

- Fan Size: 70 x 70 x 15 mm
- Heat Sink Material: Cooper.
- Cpu Type: P4 Socket 478 up to 2.8G.
- Lead Wire: 3Pins power connector.
- Option: Lighting cooling fan with LEDs.
- Application: CPU cooling.



Cooling Fan Specification:

Fan Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
701512U	12VDC	10-16VDC	0.35A	4.26W	37.5CFM	1.28mm	4000RPM	19db	51g
701512H	12VDC	10-16VDC	0.37A	4.44W	40.5CFM	1.48mm	5000RPM	21db	51g
701512M	12VDC	10-16VDC	0.16A	1.92W	21.5CFM	1.25mm	3500RPM	25db	51g

Note: Standard cooling fan model is 701512U.

CPU Cooler Specification:

Model	Fan	Base	Folded Fin	CPU Type	Connector	Interface	Life
772-67CU	701512U	Cooper	Cooper	P4 2.8G	3 Pin	Thermal-Grease	50,000Hours

Option:

1. Standard fan model in Ultra High speed, Slight or Low speed fan on request.
2. Lighting Cooler with transparent cooling fan on request.

772-67CU with Cooper cooler base and folded fins, it's design for P4 Socket 478 up to 2.8G Hz.

772-67CU standard fan motor model number is 701512U, high and medium speed fan motor are recommend for lower CPU frequency only.

On customers request, Xprovider also providing colorful lighting cooler with superbright LEDs and transparent cooling fan body.

